

## Blowout Preventer Datasheet

### Annular BOP 13-5/8" 5K

Type	Annular
Model	Shaffer
Size	13-5/8"
Pressure rating	5K
Top Connection	13-5/8" 5K Studded
Bottom Connection	13-5/8" 10K Flanged
Temperature Class Metallic	T-20
OEM certified	Yes

## Blowout Preventer Datasheet

### Annular BOP 21-1/4" 2K

Type	Annular
Model	Shaffer
Size	21-1/4"
Pressure rating	2K
Top Connection	21-1/4" 2K Studded
Bottom Connection	20-3/4" 3K Flanged
Temperature Class Metallic	T-20
OEM certified	Yes

## Blowout Preventer Datasheet

### Double BOP 13-5/8" 10K

Type	Double
Model	Cameron U
Size	13-5/8"
Pressure rating	10K
Top Connection	13-5/8" 10K Studded
Bottom Connection	13-5/8" 10K Flanged
Tandem Booster	Yes
Temperature Class Metallic	T-20
Outlet blind flanges	4x 4-1/16" 10K
Temperature Class Metallic	T-20
OEM certified	Yes

## Blowout Preventer Datasheet

### Single BOP 13-5/8" 10K

Type	Single
Model	Cameron U
Size	13-5/8"
Pressure rating	10K
Top Connection	13-5/8" 10K Studded
Bottom Connection	13-5/8" 10K Flanged
Temperature Class Metallic	T-20
Outlet blind flanges	2x 4-1/16" 10K
Temperature Class Metallic	T-20
OEM certified	Yes

## Blowout Preventer Datasheet

### Single BOP 20-3/4" 3K

Type	Single
Model	Cameron U
Size	20-3/4"
Pressure rating	2K
Top Connection	20-3/4" 3K Studded
Bottom Connection	20-3/4" 3K Flanged
Tandem Booster	optional
Temperature Class Metallic	T-20
Outlet blind flanges	2x 4-1/16" 10K
Temperature Class Metallic	T-20
OEM certified	Yes